

# Model 149

## Stratum 3E, 9x14 mm OXCO

### Features

- 10 to 50 MHz Frequency Range
- Compliant to Stratum 3E of GR-1244-CORE
- Surface Mount
- 3.3V or 5.0V operation
- Low Jitter/Phase Noise
- Tape and Reel Packaging

### Applications

- Telecom Switching
- Wireless Communication
- Timing over Packet



Part Dimensions: 9.7 × 14.9 x 7.0 mm

### Description

The CTS Model 149 is a low cost, small size, high performance OXCO. The high quality SC Quartz Crystal used in this OXCO offers high stability and low jitter/phase noise, making it the ideal choice for any telecommunications system.

### Ordering Information – Table 1

Model	Temp Range	Stability*	Supply Voltage	Electronic Freq Control	Frequency Code																																																		
1498	<u>B</u>	<u>I</u>	<u>E</u>	<u>N</u>	20M000																																																		
	<table border="1"> <thead> <tr> <th>Code</th> <th>Temp range</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>0 to 50°C</td> </tr> <tr> <td>B</td> <td>0 to 70°C</td> </tr> <tr> <td>C</td> <td>-10 to 60°C</td> </tr> <tr> <td>D</td> <td>-20 to 70°C</td> </tr> <tr> <td>G</td> <td>-40 to 85°C</td> </tr> </tbody> </table>	Code	Temp range	A	0 to 50°C	B	0 to 70°C	C	-10 to 60°C	D	-20 to 70°C	G	-40 to 85°C	<table border="1"> <thead> <tr> <th>Code</th> <th>Stability (ppb)</th> </tr> </thead> <tbody> <tr> <td>R</td> <td>±100</td> </tr> <tr> <td>T</td> <td>±50</td> </tr> <tr> <td>U*</td> <td>±20</td> </tr> <tr> <td>V*</td> <td>±10</td> </tr> <tr> <td>W*</td> <td>10 pk-pk (Std option only)</td> </tr> </tbody> </table>	Code	Stability (ppb)	R	±100	T	±50	U*	±20	V*	±10	W*	10 pk-pk (Std option only)	<table border="1"> <thead> <tr> <th>Code</th> <th>Supply</th> </tr> </thead> <tbody> <tr> <td>D</td> <td>5.0V ±5%</td> </tr> <tr> <td>E</td> <td>3.3V ±5%</td> </tr> </tbody> </table>	Code	Supply	D	5.0V ±5%	E	3.3V ±5%	<table border="1"> <thead> <tr> <th>Code</th> <th>Spec</th> </tr> </thead> <tbody> <tr> <td>V</td> <td>EFC</td> </tr> <tr> <td>N</td> <td>No EFC</td> </tr> </tbody> </table>	Code	Spec	V	EFC	N	No EFC	<table border="1"> <thead> <tr> <th>Code</th> <th>Frequency (MHz)</th> </tr> </thead> <tbody> <tr> <td>20M000</td> <td>20.000</td> </tr> <tr> <td>XXMXXX</td> <td>XX.XXX</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Standard Frequencies (MHz)</th> </tr> </thead> <tbody> <tr> <td>10.000</td> </tr> <tr> <td>12.800</td> </tr> <tr> <td>19.200</td> </tr> <tr> <td>20.000</td> </tr> <tr> <td>24.576</td> </tr> <tr> <td>25.000</td> </tr> <tr> <td>49.152</td> </tr> </tbody> </table>	Code	Frequency (MHz)	20M000	20.000	XXMXXX	XX.XXX	Standard Frequencies (MHz)	10.000	12.800	19.200	20.000	24.576	25.000	49.152
Code	Temp range																																																						
A	0 to 50°C																																																						
B	0 to 70°C																																																						
C	-10 to 60°C																																																						
D	-20 to 70°C																																																						
G	-40 to 85°C																																																						
Code	Stability (ppb)																																																						
R	±100																																																						
T	±50																																																						
U*	±20																																																						
V*	±10																																																						
W*	10 pk-pk (Std option only)																																																						
Code	Supply																																																						
D	5.0V ±5%																																																						
E	3.3V ±5%																																																						
Code	Spec																																																						
V	EFC																																																						
N	No EFC																																																						
Code	Frequency (MHz)																																																						
20M000	20.000																																																						
XXMXXX	XX.XXX																																																						
Standard Frequencies (MHz)																																																							
10.000																																																							
12.800																																																							
19.200																																																							
20.000																																																							
24.576																																																							
25.000																																																							
49.152																																																							

**Part Number Examples:**  
1498GUEV10M000

\* For full GR-1244 Stratum 3E holdover and wander generation performance, choose:  
Stability option U for compliance over any 25°C change, or  
Stability option V for compliance over any 40°C change, or  
Stability option W for compliance over -40°C/+85°C.

Note: Not all stabilities are available for all frequencies. Please consult factory.

## Electrical Specifications

Parameter	Conditions & Remarks	Min	Typical	Max	Unit	
<b>Operating Conditions</b>						
Operating Temperature Range	T <sub>OP</sub>	-40	-	85	°C	
Supply Voltage	V <sub>CC</sub> : 3.3V or 5.0V	3.135 4.75	3.3 5.0	3.465 5.25	Vdc	
Power Consumption	Warm-up Steady State; T <sub>A</sub> = 25°C	- -	- 0.7	2.7 1	W	
Load		13.5	15	16.5	pF	
<b>Frequency Stability</b>						
Frequency	F <sub>NOM</sub>	10	-	50	MHz	
Initial Frequency Tolerance	@25°C, at time of shipment	-	-	±0.200	ppm	
Freq. vs Temperature (See Table 1)	-40°C to 85°C (ref to +25C) 4°C change (option V)	- -	- -	±10 1	ppb ppb pk-pk	
Freq. vs Supply Voltage	V <sub>CC</sub> ±5%	-	±1	±5	ppb	
Freq. vs Load	15 pf ±5%	-	±1	±5	ppb	
Freq. vs Time (Aging )	After 30 days of operation (for 19.2 MHz)	- - -	- - -	±1 ±100 ±0.5	ppb/day ppb/year ppm/10 yrs	
Free run accuracy	All causes – 10 years	-	-	±1.6	ppm	
Frequency Retrace	0.5 hours on after 24 hrs off, preceded by 24 hrs on. Ref to turn off frequency.	-	-	±50	ppb	
Short Term Stability (ADEV)	1.0 sec	-	-	0.05	ppb	
Warm-up time	@ 25°C, After 5 mins referenced to the freq after 1 hour on	-	-	±50	ppb	
Holdover Stability (24 hours)	For any 40°C change over the operating temperature range (Stability options U and V. See Table 1)	-	-	11	ppb, pk-pk	
Wander Generation	Meets Stratum 3E MTIE and TDEV per Telcordia GR-1244-CORE					
<b>Output Parameters</b>						
CMOS Output Levels	3.3V (LVCMOS) 5.0V (HCMOS)	V <sub>OL</sub>	- -	- -	0.4 0.4	Vdc
		V <sub>OH</sub>	2.4 3.0	- -	- -	
Rise/Fall Times	10% to 90%, 15pf load	-	-	5	ns	
Duty Cycle	@50% of output signal	45	50	55	%	



### Electrical Specifications (Continued)

Parameter	Conditions & Remarks	Min	Typical	Max	Unit
Phase Noise (19.20 MHz)	1 Hz	-	-85	-	dBc/Hz
	10 Hz	-	-115	-	
	100 Hz	-	-138	-	
	1 kHz	-	-148	-	
	10 kHz	-	-155	-	
	100 kHz	-	-158	-	

### Electronic Frequency Control - EFC (Optional)

EFC Control Voltage	$V_C$	3.3V	0.0	1.65	3.3	Volts
		5.0V	0.0	2.5	5.0	
Frequency Adjust Range			$\pm 0.8$	-	$\pm 2.0$	ppm
Slope	Positive, monotonic		-	-	-	
Input Impedance	$Z_{IN}$		100	-	-	Kohms
Linearity			-	-	10	%

Typical Stratum 3E Wander Generation performance per Telcordia GR-1244-CORE  
(locked through a 0.001Hz loop bandwidth)




## Mechanical and Environmental

Storage Temperature Range	-55°C to +105°C
Operating Temperature Range	-40°C to +85°C
Reflow Profile	Per IPC/JEDEC J-STD-020D; >217°C, 1.5min and 245°C (Absolute max temperature), 10 secs. <b>Note:</b> This product is not designed to be reflowed in an inverted position.
Mechanical Shock	500g, 1ms, 1/2 sinewave, 3 shocks each direction along 3 mutually perpendicular planes.
Drop	10 cm height, 3 times onto hard board with thickness of 3 cm. - IEC60028-2-32 test Ed.
Bumping	40g, 6mS, 4000 ±10 times in each of three mutually perpendicular axes
Mechanical Vibration	10-55 Hz, 1.5mm DA, 55-2000Hz 10G, 30 min sweep each axis
Thermal Shock	-40°C ~ +85°C. 0.5 hour dwells with <30 second transitions. 100 cycles
RoHS	Lead Free, and fully compliant to RoHS Directive 2011/65/EU
MSL	Level 2

## Mechanical Specifications

Pad termination finish: Gold flash < 10 μ inch, over Ni plated Cu




Dimension (mm)

Symbol	Min	Max
A	-	14.9
B	-	9.7
C	-	7.0
E	1.6	1.8
F	0.9	1.1
G	2.54 nominal	
H	2.54 nominal	

Pad Connection

Pad	Connection
1	Vc or N/C
2	N/C
3	Ground
4	Output
5	N/C
6	Vcc

## Recommended Solder Pad




All dimensions are mm [inches]  
All dimensions are nominal

## Marking Key

**	Mfg site code
YYWWXXXXX	Serial Number (mfg date code = first 4 digits)


### Solder Reflow



Ts max to Tl(Ramp-up Rate)	3°C/s max
Preheat	
Temperature Min (Ts min)	150°C
Temperature typ (Ts)	175°C
Temperature max (Ts max)	200°C
Time (ts)	60-120 seconds
Ramp-up Rate (Tl to Tp)	3°C/s max
Time maintained above:	
--Temperature (Tl)	217°C
--Time (tl)	90 seconds max
Peak Temperature	245°C max for 10 seconds
Time within 5°C of peak (tp)	20 seconds
Ramp-down Rate	6°C/s max
Time 25°C to Peak Temp (t)	8 minutes max

Note: Temperatures represent device body temperature.

### Packing: Tape and Reel



This product is specified for use only in standard commercial applications. Supplier disclaims all express and implied warranties and liability in connection with any use of this product in any non-commercial applications or in any application that may expose the product to conditions that are outside of the tolerances provided in its specification.