

Features

- Low Loss
- Narrow Bandwidth
- Excellent Return Loss


Description

Pin mounted, silver (Ag) coated ceramic filter. Developed for use in TCAS applications.

Weight: 21 grams typical

Material: Filter is composed of a ceramic block plated with Ag and a bracket consisting of Olin 770 Copper Alloy (Cu, Zn, Ni)

Filter Complies with RoHS Standards



Electrical Specifications


Parameter	Frequency (MHz)	Typical @ 25°C	Spec. @ 25°C	Spec. @ -40°C to +85°C
Passband Insertion Loss	1027-1033	0.7 dB	1.0 dB max	1.2 dB max
Passband Return Loss	1027-1033	18.0 dB	14.0 dB min	12.0 dB min
Attenuation	910	44.0 dB	40.0 dB min	40.0 dB min

Note: Supplier shall test each filter to the critical electrical specifications of the above table. Any subsequent audits may deviate from in value due to measurement repeatability among different test systems. Such deviations shall not exceed the following limits:


Specification Allowance	
Insertion Loss	0.1 dB
Return Loss	1.0 dB
Stopbands	1.0 dB

Mechanical Drawing


Preliminary A – Origin Date: July 22, 2015– Revision Date: Dec 16, 2021



Electrical response



PCB Layout



Packaging and Marking

This product is shipped in pre-formed foam trays.

