

UPB079A


4400-5000MHz UPB Series TDD Bandpass Filter

Features

- Low Loss with High Rejection
- Low ripple
- Universal footprint across family for all TDD bands

Applications

- Wireless Infrastructure applications
- High-performance carrier-grade single-band TDD Pico-cell basestations for up to 1.0W at the antenna port.



Part Dimensions: 9.2 × 5.0 × 3.1 mm • 0.38 g

Materials: Ag plated ceramic block with fused-tin plated brass shield

Description

Surface mount ceramic bandpass filter supports a universal footprint across all TDD frequency bands enabling the use of a common system PCB. Superior rejection, insertion loss, reliability, as well as both peak and average power handling compared other bandpass filter technologies.

Electrical Specifications

Parameter	Frequency (MHz)	Typical at 25°C	Spec. at 25°C	Spec. over -40°C to +85°C
Nominal Impedance	-	50 ohms	-	-
Average Input Power	-	-	-	2.0 Watt max
Peak Input Power	-	-	-	20 Watt max

Input-Output Response


Passband Insertion Loss (100 MHz avg)	4400-5000	1.2 dB	1.3 dB max	1.4 dB max
Passband Ripple	4400-5000	1.0 dB	1.2 dB max	1.3 dB max
Passband Return Loss	4400-5000	13 dB	10 dB min	10 dB min
Attenuation:	1-2700	50 dB	40 dB min	40 dB min
	2701-3800	45 dB	30 dB min	30 dB min
	5150-7125	32 dB	30 dB min	30 dB min

Note: CTS tests each unit to the critical specifications above. Subsequent audits may deviate due to repeatability among different test systems which shall not exceed these allowances.

Specification Allowance


Insertion Loss	0.1 dB
Return Loss	1.0 dB
Attenuation	1.0 dB

Mechanical Drawing



Dim.	Nominal (mm)	Tolerance (±mm or Max)
A	8.97	0.20
B	3.80	max
C	0.76	0.13
D	0.38	0.13
E	0.38	0.13
F	1.80	0.13
G	6.60	0.13
H	3.10	max
I	0.76	0.13
J	1.00	0.20

PCB Layout



IMPORTANT: Please assure ≥ 30 mils (0.75mm) thickness of dielectric beneath the I/O Pads and the surrounding clearance zone down to the required ground plane.

Please assure sufficient ground vias between the top metal ground plane and the primary ground plane.


Recommended solder: 4-6 mils of SAC305 with reflow including 120s of soak at 217°C, and up to 30 sec peak at 241°C.

NOTE: A width of 9.50mm is necessary to support frequencies as low as 1885MHz for Band 39. If only higher frequency TDD bands are supported, then this smaller space can be allocated on the layout.

Packaging and Marking

Dimension	Units	Spec.	Product Marking
Reel Diameter	mm	330	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> CTS 079 YWW </div>
Reel Weight	kg	5.5	
Reel Quantity	ea.	500	

Customer Feed Direction → →



W_0	A_0	B_0	K_0	P_0
0.630 in 16.0 mm	0.205 in 5.20 mm	0.366 in 9.30 mm	0.132 in 3.35 mm	0.472 in 12.0 mm

Electrical Response

