



USB207A - Preliminary

2025-2110MHz USB Series TDD BPF

Features

- Low Loss with High Rejection
- Universal footprint across family for all TDD bands

Applications

- Specialty Wireless applications
- High-performance demanding field deployments



Part Dimensions: 25.7 x <8.6 x 6.7 mm • <4.2 g
Materials: Ag plated ceramic block with fused-tin plated brass shield

Description

Surface mount ceramic bandpass filter supports a universal footprint across all TDD frequency bands enabling the use of a common system PCB. Superior rejection, insertion loss, reliability, as well as both peak and average power handling compared to other bandpass filter technologies.


Electrical Specifications

Parameter	Frequency (MHz)	Typical at 25°C	Spec. at 25°C	Spec. over -40°C to +85°C
Nominal Impedance	-	50 ohms	-	-
Average Input Power	-	-	-	5.0 Watt max
Peak Input Power	-	-	-	50 Watt max
Input-Output Response				
Passband Insertion Loss (5 MHz avg)	2025-2110	1.1 dB	1.3 dB max	1.4 dB max
Passband Ripple	2025-2110	0.4 dB	0.9 dB max	0.9 dB max
Passband Return Loss	2025-2110	16 dB	14 dB min	14 dB min
Attenuation:	2200-2300		45 dB min	45 dB min

Note: CTS tests each unit to the critical specifications above. Subsequent audits may deviate due to repeatability among different test systems which shall not exceed these allowances.


Specification Allowance	
Insertion Loss	0.1 dB
Return Loss	1.0 dB
Attenuation	1.0 dB

Mechanical Drawing



Dim.	Nominal (mm)	Tolerance (±mm or Max)
A	25.90	max
B	6.70	0.30
C	1.70	0.13
D	0.80	0.13
E	0.80	0.13
F	4.20	typ
G	16.90	0.13
H	6.70	max
I	1.00	0.13
J	1.60	max

PCB Layout



IMPORTANT: Please assure ≥ 20 mils (0.5mm) thickness of dielectric beneath the I/O Pads and the surrounding clearance zone down to the ground plane.

Please assure sufficient ground vias between the top metal ground plane and the primary ground plane.


Recommended solder: 4-6 mils of SAC305 with reflow including 120s of soak at 217°C, and up to 30 sec peak at 241°C.

NOTE: The width of 9.50mm is necessary to support frequencies as low as 1885MHz for Band 39. If only higher frequency TDD bands are supported, then a smaller space can be allocated on the layout.

Packaging and Marking

Dimension	Units	Spec.	Product Marking
Reel Diameter	mm	330	CTS
Reel Weight	kg	5.5	207
Reel Quantity	ea.	500	YWW

Customer Feed Direction → → →



W_0	A_0	B_0	K_0	P_0
1.732 in 44.0 mm	0.xxx in x.xx mm	1.028 in 26.10 mm	0.283 in 7.20 mm	0.472 in 12.0 mm

Electrical Response

