

# USB395CB

## 3.7-4.2GHz USB Series TDD Bandpass Filter

### Features

- Low Loss with High Rejection and Low Ripple
- Universal footprint across family for all TDD bands

### Applications

- Wireless Infrastructure applications
- High-performance carrier-grade single-band TDD Pico-cell basestations for up to 5.0W at the antenna port.



Part Dimensions: 25.9 × 5.0 × 6.7 mm • 2.2 g  
Materials: Ag plated ceramic block with tin plated brass shield

### Description

Surface mount ceramic bandpass filter supports a universal footprint across all TDD frequency bands enabling the use of a common system PCB. Superior rejection, insertion loss, reliability, as well as both peak and average power handling compared to other bandpass filter technologies.

### Electrical Specifications

Parameter	Frequency (MHz)	Typical at 25°C	Spec. at 25°C	Spec. over -40°C to +85°C
Nominal Impedance	-	50 ohms	-	-
Average Input Power	-	-	-	5.0 Watt max
Peak Input Power	-	-	-	50 Watt max


#### Input-Output Response

Passband Insertion Loss (20 MHz avg)	3700-4200	0.9 dB	1.1 dB max	1.1 dB max
Passband Return Loss	3700-4200	14 dB	12 dB min	12 dB min
Attenuation:	1-3400	50 dB	45 dB min	45 dB min
	4600-5950	46 dB	40 dB min	40 dB min

Note: CTS tests each unit to the critical specifications above. Subsequent audits may deviate due to repeatability among different test systems which shall not exceed these allowances.


Specification Allowance	
Insertion Loss	0.1 dB
Return Loss	1.0 dB
Attenuation	1.0 dB

### Mechanical Drawing



Dim.	Nominal (mm)	Tolerance (±mm or Max)
A	25.90	max
B	3.70	max
C	1.70	0.13
D	0.80	0.13
E	0.80	0.13
F	4.20	0.13
G	16.90	0.13
H	6.70	max
I	1.00	0.13
J	1.10	0.20

### PCB Layout



**IMPORTANT:** Please assure  $\geq 30$  mils (0.75mm) thickness of dielectric beneath the I/O Pads and the surrounding clearance zone down to the ground plane.

Please assure sufficient ground vias between the top metal ground plane and the primary ground plane.


Recommended solder: 4-6 mils of SAC305 with reflow including 120s of soak at 217°C, and up to 30 sec peak at 241°C.

**NOTE:** The width of 9.50mm is necessary to support frequencies as low as 1885MHz for Band 39. If only higher frequency TDD bands are supported, then a smaller space can be allocated on the layout.

### Packaging and Marking

Dimension	Units	Spec.	Product Marking
Reel Diameter	mm	330	CTS
Reel Weight	kg	5.5	95C
Reel Quantity	ea.	500	YYWW

Customer Feed Direction → → →



$W_0$	$A_0$	$B_0$	$K_0$	$P_0$
1.732 in 44.0 mm	0.209 in 5.30 mm	1.028 in 26.10 mm	0.283 in 7.20 mm	0.472 in 12.0 mm

### Electrical Response

