

# USB480B - PRELIMINARY

## 4700-4900MHz USB Series TDD Bandpass Filter

### Features

- Low Loss with High Rejection and Low Ripple
- Support for 3GPP Receive Blocker specification
- Universal footprint across family for all TDD bands



### Applications

- Wireless Infrastructure applications
- High-performance carrier-grade single-band TDD Pico-cell basestations for up to 5.0W at the antenna port.

Part Dimensions: 25.7 × 4.8 × 6.6 mm • 2.5 g  
Materials: Ag plated ceramic block with tin plated brass shield

### Description

Surface mount ceramic bandpass filter supports a universal footprint across all TDD frequency bands enabling the use of a common system PCB. Superior rejection, insertion loss, reliability, as well as both peak and average power handling compared to other bandpass filter technologies.

### Electrical Specifications

Parameter	Frequency (MHz)	Typical at 25°C	Spec. at 25°C	Spec. over -40°C to +85°C
Nominal Impedance	-	50 ohms	-	-
Average Input Power	-	-	-	8.0 Watt max
Peak Input Power	-	-	-	80 Watt max

#### Input-Output Response


Passband Insertion Loss (5 MHz avg)	4700-4900	1.7 dB	1.9 dB max	2.0 dB max
Passband Ripple (20MHz)	4700-4900	1.2 dB	1.4 dB max	1.5 dB max
Passband Return Loss	4700-4900	14 dB	12 dB min	12 dB min
Attenuation:	1-2690	43 dB	40 dB min	40 dB min
	2691-4200	38 dB	35 dB min	35 dB min
	4201-4680	8 dB	6 dB min	6 dB min
	4920-5149	8 dB	6 dB min	6 dB min
	5150-5549	33 dB	30 dB min	30 dB min
	5550-TBD	43 dB	38 dB min	38 dB min

Note: CTS tests each unit to the critical specifications above. Subsequent audits may deviate due to repeatability among different test systems which shall not exceed these allowances.

#### Specification Allowance


Insertion Loss	0.1 dB
Return Loss	1.0 dB
Attenuation	1.0 dB

### Mechanical Drawing



Dim.	Nominal (mm)	Tolerance (±mm or Max)
A	25.40	0.30
B	3.40	0.30
C	1.70	0.13
D	0.80	0.13
E	0.80	0.13
F	4.20	0.13
G	16.90	0.13
H	6.40	0.20
I	1.00	0.13
J	0.90	0.20

### PCB Layout




IMPORTANT: Please assure  $\geq 20$  mils (0.5mm) thickness of dielectric beneath the I/O Pads and surrounding clearance zone to the required ground plane.

NOTE: The width of 9.50mm is necessary to support frequencies as low as 1885MHz for Band 39. If only higher frequency TDD bands are supported, then a smaller space can be allocated on the layout.

### Packaging and Marking

Dimension	Units	Spec.	Product Marking
Reel Diameter	mm	330	CTS
Reel Weight	kg	5.5	480B
Reel Quantity	ea.	500	YWW

Customer Feed Direction → → →



$W_o$	$A_o$	$B_o$	$K_o$	$P_o$
1.732 in 44.0 mm	0.209 in 5.30 mm	1.028 in 26.10 mm	0.283 in 7.20 mm	0.472 in 12.0 mm

### Electrical Response

