

## UMD066A - Preliminary Band 66 UMD Series Duplexer

### Features

- Low Loss with High Rejection
- Superior power handling and reliability
- Universal footprint across all UMD Series frequency bands
- Available for either PCB mounting or with various connectors including SMA, SMP-Max, and other options.



Available as direct-solder to PCB or with various connector options.

ESTIMATE Part Dimensions: 64 × 29 × 13 mm • <90 g (excl. connectors)  
Materials: Ag plated ceramic block with tin plated brass shield

### Applications

- Wireless Infrastructure applications
- High-performance carrier-grade active antennas and small-cells for 4-10W at the antenna port.
- Wide-band DAS, Repeaters, or small-cells requiring multi-channel or carrier aggregation

### Description

Ceramic duplexer supports a universal footprint across all FDD frequency bands enabling the use of a common system PCB. Provides superior rejection, insertion loss, reliability, as well as both peak and average power handling compared to other duplexer technologies.

### Electrical Specifications

Parameter	Frequency (MHz)	Typical at 25°C	Spec. at 25°C	Spec. over -40°C to +85°C
Nominal Impedance	-	50 ohms	-	-
Average Input Power	-	-	-	20.0 Watt max
Peak Input Power	-	-	-	200 Watt max
Passive Intermodulation (2x 5W)	-	-	-	-106 dBm TBC

#### Antenna to UL Response

Passband Insertion Loss (5 MHz avg)	1710 - 1780			1.8 dB max
Passband Return Loss	1710 - 1780	15 dB	14 dB min	14 dB min
Attenuation:	2110 - 2200	74 dB	72 dB min	72 dB min

#### DL to Antenna Response

Passband Insertion Loss (5 MHz avg)	2110 - 2200			1.8 dB max
Passband Return Loss	2110 - 2200	15 dB	14 dB min	14 dB min
Attenuation:	1710 - 1780	80 dB	78 dB min	78 dB min

#### DL to UL Response

Attenuation for UL band	1710 - 1780	82 dB	80 dB min	80 dB min
Attenuation for DL band	2110 - 2200	76 dB	74 dB min	74 dB min

Note: CTS tests each unit to the critical specifications above. Subsequent audits may deviate due to repeatability among different test systems which shall not exceed these allowances.

Specification Allowance	
Insertion Loss	0.1 dB
Return Loss	1.0 dB
Attenuation	1.0 dB


TBC = To be confirmed









## Band 66 UMD Series Duplexer

Dim.	Nominal (mm)	Tolerance (±mm or Max)
A	64.00	Max
B	29.00	Max
C		
D		
E		
F		
G		
H		
I		
J		
K		


## PCB Layout (Top-Down View)



----- Filter Outline

	Exposed Conductor for Surface Mount		Solder Resist Over Conductor (Keep Out Area)
	Exposed Conductor for SMP-MAX Connector		Solder Resist over Dielectric
	Pin for Pinpoint		Via for Pin Mount

## Packaging and Marking



Product is shipped in  
Pre-formed foam trays

## Electrical Response

## Simulation

The trays have xx slots each with one filter per slot. Boxes are packed with 12 Trays per box for a total of xx filters per box.



## Electrical Specifications – Supplemental Spectrum Specifications

Parameter	Frequency (MHz)	Typical at 25°C	Spec. at 25°C	Spec. over -40°C to +85°C
Antenna to UL Response				
Attenuation:	1 - 960			60 dB min
	961 - 1511			48 dB min
	1930 - 2025			48 dB min
	2300 - 2690			48 dB min
DL to Antenna Response				
Attenuation:	1 - 1709			60 dB min
	1850 - 1920			48 dB min
	2300 - 2690			48 dB min

## Ordering Options

Part Number	Code	Connector Option Description
UMD066A	[blank]	No pins or connectors
	-C3	3 SMP-Com Male with limited detent
	-CF2	SMP-Com Male with limited detent antenna port + 2 SMP female cables
	-M3	3 SMP-Max Slide-type Male
	-P3	3 thru-hole pins for soldering to PCB
	-S3	3 SMA Female