

*By Erling Ringgaard, Tomasz Zawada, Louise M. Bierregaard, Michele Guizzetti, Ruichao Xu.*

## Presentation (IEEE ISAF)

Energy harvesting is a field of research that has attracted considerable interest for more than a decade. It can be defined as the technology of devices that transform low-grade energy such as solar energy, vibrations, thermal energy and weak electromagnetic fields into usable electrical energy. Energy harvesting is a key enabling technology for modern wireless sensors where avoiding a battery is either crucial or gives an important competitive edge. The present work deals with vibrational energy harvesting where the input energy is kinetic (acceleration or strain) and the focus will be on piezoelectric ceramic materials. A number of ceramic technologies will be compared - thick films integrated with MEMS, tape casting and conventional bulk ceramics - and relevant generator designs will be considered in each case. When it comes to choosing a suitable piezoelectric material, a number of functional properties need to be taken into account and these are conventionally combined into a single figure-of-merit, depending on the operation mode (low frequency or resonant). This concept will be here to compare a number of piezoceramic materials, including various types of doped PZT and some lead-free compositions. The performance of various energy harvesting generators manufactured by this group will be summarized in terms of open-circuit voltage and output power as a function of excitation frequency and amplitude, and a comparison with results from the literature will be given.

## Contact Information

[Contact Page](#)

([www.ctscorp.com/Contact-Us/](http://www.ctscorp.com/Contact-Us/))

CTS Corporation

4925 Indiana Avenue, Lisle

IL 60532, USA

Web: [www.ctscorp.com](http://www.ctscorp.com)

E-mail: [sales@ctscorp.com](mailto:sales@ctscorp.com)