


Contact Transducers

Fingertip Contact Transducers

Fingertip Contact Transducers are small diameter contact transducers ideally suited for limited access surface inspections or when higher frequencies are needed. These Fingertip Contact Transducers are offered with right angle microdot connectors.



FREQUENCY (MHz)	DIAMETER INCHES (mm)				
	0.25 (6.35)	0.375 (9.525)	0.5 (12.7)	0.75 (19.05)	1.00 (25.4)
TYPE GP: GENERAL PURPOSE					
1.00	CF0102GP	CF0103GP	CF0104GP	CF0106GP	CF0108GP
2.25	CF0202GP	CF0203GP	CF0204GP	CF0206GP	CF0208GP
3.50	CF0302GP	CF0303GP	CF0304GP	CF0306GP	CF0308GP
5.00	CF0502GP	CF0503GP	CF0504GP	CF0506GP	CF0508GP
7.50	CF0702GP	CF0703GP	CF0704GP	–	–
10.00	CF1002GP	CF1003GP	CF1004GP	–	–
TYPE HR: HIGH RESOLUTION					
1.00	–	–	CF0104HR	CF0106HR	CF0108HR
2.25	CF0202GP	CF0203GP	CF0204GP	CF0206GP	CF0208GP
3.50	CF0302GP	CF0303GP	CF0304GP	CF0306GP	CF0308GP
5.00	CF0502GP	CF0503GP	CF0504GP	CF0506GP	CF0508GP
7.50	CF0702GP	CF0703GP	CF0704GP	–	–
10.00	CF1002GP	CF1003GP	CF1004GP	–	–
TYPE HP: HIGH POWER					
1.00	–	CF0103GP	CF0104GP	CF0106GP	CF0108GP
2.25	CF0202GP	CF0203GP	CF0204GP	CF0206GP	CF0208GP
3.50	CF0302GP	CF0303GP	CF0304GP	CF0306GP	CF0308GP
5.00	CF0502GP	CF0503GP	CF0504GP	CF0506GP	CF0508GP
7.50	CF0702GP	CF0703GP	CF0704GP	–	–
10.00	CF1002GP	CF1003GP	CF1004GP	–	–