

**Features**

- Low Loss
- Low Ripple
- High Rejection


**Description**

Surface mount, silver (Ag) coated ceramic diplexer. Developed for use in Small Cell Wireless Infrastructure applications.

Weight: 20.8 grams typical

Material: Filter is composed of a ceramic block plated with Ag and a shield made of nickel silver plated steel.

Filter complies with RoHS standards.



**Electrical Specifications**

Parameter	Frequency (MHz)	Typical @ 25°C	Spec. @ 25°C	Spec. over -40°C to +85°C
<b>Low Band</b>				
Passband Insertion Loss	1710 - 1880	1.0 dB	1.2 dB max	1.4 dB max
Passband Return Loss	1710 - 1880	18.0 dB	16.0 dB min	16.0 dB min
Attenuation:	1920 - 2170	35.0 dB	30.0 dB min	30.0 dB min
<b>High Band</b>				
Passband Insertion Loss	1920 - 2170	1.0 dB	1.2 dB max	1.4 dB max
Passband Return Loss	1920 - 2170	18.0 dB	16.0 dB min	16.0 dB min
Attenuation:	1710 - 1880	35.0 dB	30.0 dB min	30.0 dB min
<b>Average Power</b>				10 Watt max
<b>Peak Power</b>				100 Watt max


Note: Supplier shall test each filter to the critical electrical specifications of the above table. Any subsequent audits may deviate from in value due to measurement repeatability among different test systems. Such deviations shall not exceed the following limits:

Specification Allowance	
Insertion Loss	0.1 dB
Return Loss	1.0 dB
Stopbands	1.0 dB

\*This product is covered by one or more of the following U.S. and foreign patents including: US 4,692,726;US 4,742,562; US 4,800,348;US 4,829,274;US 5,146,193;EP 0573597;DE 0573597;FR 0573597;JP 508149/92;KR 142171;US 5,162,760;US 5,218,329;US 5,250,916;US 5,327,109;US 5,488,335;CA 2114029;FR 9306297;GB 2273393;JP 3205337;KR 115113;CN 93106228.4;US 5,512,866;EP 0706719;DE 0706719;FR 0706719;GB 0706719;CN 95190359.4;US 5,602,518;US 5,721,520;US 5,745,018;EP 0910875;DE 0910875;DK 0910875;FR 0910875;GB 0910875;IE 0910875;JP 505182/98;KR 10-323013;US 5,994,978;US 6,462,629;CN 00810420.4;US 6,559,735;US 6,650,202;US 6,834,429. Other US and foreign patents pending.


\*CTS Corporation 2006 reserves all copyrights in the layout, design and configuration of the patterns on this product.\*

### Mechanical Drawing




Dim	Nominal (mm)	Tolerance (mm) +/- or max
A	61.40	Max
B	6.80	Max
C	2.03	0.13
D	1.27	0.13
E	6.49	0.13
F	24.21	0.13
G	24.21	0.13
H	10.90	Max
I	2.03	0.13
J	1.27	0.13
K	2.00	0.13


### PCB Layout



### Packaging and Marking




Product is shipped in preformed foam trays



The trays have 12 slots each with 2 filters per slot. Boxes are packed with 5 Trays per box for a total of 120 filters per box.

### Electrical response



Marker	1	2	3	4
Freq[GHz]	1.71	1.88	1.92	2.17
S11[dB](1)	-26.9	-24.1	-31.3	-22
S21[dB](1)	-84.8	-33.7	-1.19	-0.337
S13[dB](1)	-0.58	-1.05	-30	-71.4